

# PRODUCT DATA SHEET

7861 Airport Highway, Pennsauken, NJ 08109 • (800)346-4378 • Sales@seminolewire.com

 Part Number:
 3063
 Application:
 RF Communication

 Description:
 RG-8X, NON MIGRATING
 Approvals/Ratings:
 n/a

#### Construction & Specifications

Conductor: 16 AWG (0.058") Bare Copper

**Stranding:** 19/29 (0.0113")

# of Conductors: 1

**Dielectric:** Foam Polyethylene


Dielectric Diameter: 0.155"

**Braid:** Tinned Copper (95% Coverage) **Shield:** Bonded Aluminum (100% Coverage)

Ripcord: n/a

Jacket: Non-Migrating PVC

Overall Diameter: 0.242"



## Electrical & Environmental & Physical Properties





Minimum Bend Radius: 2.5 in. Velocity of Propagation: 76 %

**Impedance:**  $50 \Omega$  **Capacitance:** 28.5 pF/ft

Inductance: 0.065 uH/ft

Conductor DC Resistance @ 20°C: 4.3 Ω/1000ft

Attenuation:

Frequency (MHz)	1	10	30	50	150	450	900	1000
Attenuation (dB/100')	0.2	0.78	1.5	2.05	3.6	6.3	9.07	10
Attenuation (dB/100m)	0.7	2.6	4.9	6.7	11.8	20.7	29.7	32.8

## Miscellaneous Information

Insulation Color\*: White

Jacket Color\*: Black; White

Print\*: JSC WIRE AND CABLE #3063 Flexible Low Loss RG-8X Direct Burial Class IIA Jacket RoHS PROUDLY MADE IN THE USA

<seq. ft>

Weight: ≈ 37.2 Lbs/1000 feet
Put Up Length\*: 500 feet, 1000 feet

Put Up Type\*: Plastic Spools; Wood Spools

Packaging Type\*: Corrugated Boxes; Domestic Wood Pallets

### Disclaimer

The information provided in this Product Data Sheet ("Data Sheet") is intended for informational purposes only, is subject to change without notice, and is believed to be accurate as of the version date. This Data Sheet contains proprietary information, intellectual property, and confidential information belonging to Seminole Wire and Cable and/or JSC Wire and Cable (hereinafter collectively referred to as "Seminole"). The information contained in this Data Sheet shall not be disclosed, in whole or part, to any party without the prior written consent of Seminole. Seminole assumes no responsibility or liability for any information contained in this Data Sheet or the use of such information. The use of any information in this Data Sheet does not grant or confer any rights to any party, whether with regard to the information itself or anything described by such information. Since the use of the product described in this Data Sheet is not within the control of Seminole, it is the user's obligation to determine the suitability of the product for its intended application and to assume all risk and liability for its safe use.

<sup>\*</sup>Items can be customized. The customer accepts all factory lengths and +/- 10 percent of total order required.